

## Model Name:

### Monitored PDU

Monitor PDU can monitor the total power usage information from the remote end through the Internet to fully understand the power consumption of all the devices. Set up overload event alerts and notify managers via Email and TRAP, allowing managers to respond to crises in the shortest possible time to minimize disasters.

Some monitor PDU has one environmental sensor ports that track climate information: temperature and humidity environment variables. The data is available from any web browser and is SNMP-compliant for easy tracking of critical data without the use of any external software.

Provide central management software, which can manage a large number of PDUs' power information. The database stores the power consumption information of the power strip and provides the history curve chart for the manager's reference.

## Features:

### System Function:

- Built-in embedded system:  
Support 10M Ethernet interface, provides webpage and SNMP remote management.
- Multiple protocols:  
Support ICMP, ARP, IP, TCP, UDP, DHCP, HTTP, NTP, SNMP v1.
- Local display information:  
Seven-segments can display current and IP address.

### Power Management:



REMOTE  
MONITOR

#### Remote Monitor

Remote monitoring PDU status by web and SNMP



CURRENT  
MEASUREMENT

#### Current Measurement

Measure PDU total current consumption.



THRESHOLD  
SENSING

#### Threshold Sensing

User-definable warning and overload threshold value as the basis for alarm.



MAIL  
NOTIFICATION

#### Mail Notification

Notify specified user by mail and SNMP when outlet action or current over threshold.



OVERLOAD  
PROTECTION

#### Overload Protection

When overload, circuit breaker will automatically trip to protect the safety of electricity.



EVENT  
ALERT

#### Event Alert

When current exceeds the preset threshold, PDU will beep and LED will flash.



CENTRAL  
MANAGEMENT

#### Central Management

Free centralized monitoring software, real-time monitoring of a large number of PDU, provide data records and history chart.

## Model Number:

**MTH-1023J-08N1**



## Specification

<b>Output</b>		<b>Input</b>	
Voltage	200-240 VAC	Voltage	200-240 VAC
Max. Current	10 A	Frequency	50/60Hz ,full range
Outlet	(8) C13	Max. Capacity	2400 VA
Overload Protection	(1) 10A UL1077 breaker	Connection	C14. Detachable Power cord
<b>Measurement</b>		<b>Other</b>	
Current	+/-2%+/-0.1A @0.2A ~ 20 A	Ethernet	(1) RJ45
		Function Selection	(1) Button
		DHCP Ind.	(1) Green LED
		Info. Display	3 digits of 7 Segments
<b>Dimension/Weight</b>		<b>Operation</b>	
Net size	432 x 90 x 44 mm	Operation Temp.	0 ~ 45°C
Net weight	1.9 kg	Operation Humid.	0% ~ 90% RH
Package Size	505 x 210 x 90 mm	Storage Temp.	-20°C ~ 65°C
Package Weight	2.2 kg	Storage Humid.	0% ~ 90% RH
<b>Approval</b>			
Certification	CE		
Warranty	2 years		

## Package

No.	Description.
1	PDU 1 set
2	Rack mount accessories 1 set
3	Power cord, C19 to C14, 3 m
4	Software, manual, MIB by link below



## Optional Accessory

Model Number	Model Name
STR-C14-B	C13 socket protection



## Line Drawing

