

Model Name:

Basic PDU

Features:

Power Management:



Overload Protection

When overload, circuit breaker will automatically trip to protect the safety of electricity.

Model Number:

PBH-3240C-06N6

Front view



Back view



Plug



Specification

Output

Voltage	200-240 VAC
Max. Current	32 A / phase
Outlet	(6) C19
Overload Protection	(6) 16A UL489 breaker

Measurement

None

Dimension/Weight

Net size	432 x 216 x 44.5 mm
Net weight	4.0 kg
Package Size	490 x 330 x 155 mm
Package Weight	4.6 kg

Approval

Certification	CE
Warranty	2 years

Input

Voltage	400 VAC, 3 Phase 3P+N+PE
Frequency	50/60Hz, full range
Max. Capacity	22 kVA
Connection	IEC309, power cord, 3m

Other

None

Operation

Operation Temp.	0 ~ 45°C
Operation Humid.	0% ~ 90% RH
Storage Temp.	-20°C ~ 65°C
Storage Humid.	0% ~ 90% RH

Package

No.	Description.
1	PDU 1 set
2	Rack mount accessories 1 set
	

3 Manual by link below



Optional Accessory

Model Number	Model Name
STR-C20-B	C19 socket protection
	

Line Drawing

