

Platform Features Comparison

Model	Bravo (C400)	Elite	Elite adv.
Ethernet	10 Base-T	10/100 Base-T	10/100 Base-T
IP version	IPv4	IPv4 / IPv6	IPv4 / IPv6
SNMP	SNMP v1	SNMP v1 v2 v3	SNMP v1 v2 v3
User Count	1 user	8 users	8 users
Web Security	-	SSLv3, TLS 1.2	SSLv3, TLS 1.2
Command Line	-	SSH/Telnet	SSH/Telnet
Firmware Upgrade	-	Yes	Yes
Outlet Action by Event	-	Yes	Yes
Log	-	Data/Event	Data/Event
Multi-Languages	-	Multiple languages	Multiple languages
Current Precision	2%	1%	1%
Current Measurement	PDU/Outlet (Max. 8)	PDU/Outlet (Max. 24)	PDU/Outlet (Max. 24)
kWh Measurement	PDU	PDU	PDU
kWh Precision	1%	1%	1%
Temp./Humidity	1 x ENV	Up to 2 x ENV	Up to 2 x ENV
DIDO ready (Optional)	-	4 x DI, 4 x DO	4 x DI, 4 x DO
Display	7 segments	7 segments	OLED
Daisy Chain	No	No	up to 8