

## Model Name:

### Elite ATS/POM (Automatic Transfer Switch)

Elite ATS is a single phase and dual input rack mountable power distribution unit (PDU). When Input A falls below pre-set working voltage and Input B is valid, the output is automatically transferred to Input B. The output is transferred back to Input A when Input A is valid. This high speed transfer rate ensures that the transfer is transparent to the sensitive equipment. The two sources are not required to be in phase. This is an effective solution that builds in redundancy and increases the AC power availability of connected equipment. If the dual input power is fed through two independent AC sources, then the system availability is increased and the dual input advantages are fully used.

ATS provides remote manual control of the critical devices by clicking on a few buttons on the smart phone or computer webpage. Stop the problem device by cutting off the power to a specific outlet. By cycling the power off and restarting the device remotely, you save time and money by eliminating the need to send technicians to the root cause of the problem.

Managers can monitor the power usage information of each output port from the remote end through the Internet to fully understand the power consumption of all the devices. Set up overload event alerts and notify managers via Email and TRAP, allowing managers to respond to crises in the shortest possible time to minimize disasters.

ATS has two environmental sensor ports that track climate information: temperature and humidity environment variables. The data is available from any web browser and is SNMP-compliant for easy tracking of critical data without the use of any external software.

Provide central management software, which can manage a large number of PDUs' power, temperature and humidity information. The database stores the power consumption information of the power strip and provides the history curve chart for the manager's reference.

## Features:

### System Function:

- Built-in embedded system:  
Support 10/100M Ethernet interface, provides webpage and SNMP remote management.
  - Local display information:  
OLED displays current, voltage, kWh, IP address and temperature and humidity.
  - Multiple protocols:  
Support ICMP, ARP, IP, TCP, UDP, DHCP, HTTP, HTTPS, FTP, NTP, SNMP v1/2/3, TLS1.2, IPv4 and IPv6, Telnet, SSHv2
  - Management Account Certification:  
Radius certification support.
  - Multi-account management:  
Multi-group account management system. And provide three-tier permission management.
  - IP filtering:  
Support IP filtering, improve network security mechanisms.
  - Power record:  
Store up to 100000 power and event data.
  - Remote firmware upgrade:  
Provides remote firmware upgrade mechanism.
  - System operation message:  
Send the normal operation of the message automatically by trap.
  - Hardware key definition:  
User-definable button function.
  - Temperature unit conversion:  
Temperature units can choose Celsius or Fahrenheit
  - System configuration restore:  
Support the output of the system settings, to easily deploy a large amount of the same model of PDU.
  - Multilingual Support:  
Support Chinese, English, French, German, Spanish, Russian, Czech, Arabian, Persian.
-

**Power Management:**



REMOTE MONITOR

**Remote Monitor**

Remote monitoring PDU status by web and SNMP



POWER REDUNDANT

**Power Redundant Protection**

Dual power input. When the main power fails, it will automatically switch to standby power in an instant.



CURRENT MEASUREMENT

**Current Measurement**


Measure PDU total current consumption.



REMOTE CONTROL

**Remote Control**

Remote per outlet on/off by web and SNMP.



THRESHOLD SENSING

**Threshold Sensing**

User-definable warning and overload threshold value as the basis for alarm.



MAIL NOTIFICATION

**Mail Notification**

Notify specified user by mail and SNMP when outlet action or current over threshold.



POWER SEQUENCE

**Power Sequence**

User-definable power on/off sequence time.



EVENT ALERT

**Event Alert**

When current exceeds the preset threshold, PDU will beep and LED will flash.



PING EVENT CONTROL

**Ping Event Control**

When the specified IT device does not respond to PING, the output will perform a preset power action.



SCHEDULE CONTROL

**Schedule Control**

Timed & scheduled on/off/reboot control.



GROUP CONTROL

**Group Control**

Set multiple outlets as a single group while controlling the power output.



OVERLOAD PROTECTION

**Overload Protection**

When overload, circuit breaker will automatically trip to protect the safety of electricity.



EVENT REACTION

**Event Reaction**

Outlet action via pre-set event, including power, environment event and receiving trap from other device.



PER OUTLET MONITOR

**Outlet-Level Monitor**

Remote per outlet current monitoring.



ENVIRONMENT DETECTION

**Environment Detection**

Optional accessory probe to detect temperature and humidity.



KWH MEASUREMENT

**kWh Measurement**

Voltage, frequency, power factor, active power, apparent power and kWh measurement.



CENTRAL MANAGEMENT

**Central Management**

Free centralized monitoring software, real-time monitoring of a large number of PDU, provide data records and history chart.



Breaker Detection

**Circuit Breaker Detection**

PDU can detect whether breaker is tripped due to the power event. Display and notify the manager of breaker status accordingly



Manual Transfer

**Input Selection by Manually**

Input sources can be switched manually through the buttons on the panel.

## Model Number:

**APK-3011M-08N2**

Front view



Back view



Plug



## Specification

Output		Input	
Voltage	100-127 VAC	Voltage	100-127 VAC
Max. Current	30 A	Frequency	50/60Hz, full range
Outlet	(8) 5-15/20R	Max. Capacity	3810 VA
ON/OFF Ind.	(8) Green LED	Connection	(2) L5-30P, power cord, 3m
Threshold Ind.	(8) Red LED	Input Status	(2) Green LED
Output Status	(2) Green LED		
Circuit Ind.	(2) Red LED		
Overload Protection	(2) 15A UL489 breaker		
Measurement		Other	
Current	+/-1%+/-0.1A @0.2A ~ 20 A	Transfer Time	8~16ms
Voltage	+/- 1% +/- 1V @80V~260V	ENET Connection	(1) RJ45
Active Power	+/- 1% +/- 5W @50W~8000W	ENV Connection	(2) RJ11
Apparent Power	+/- 1% @50VA~8000VA	Function Selection	(1) Button
Frequency	+/- 1% @50~65Hz	Daisy Chain	(2) RJ22
Power Factor	+/- 1% @0.1~1.0	WIFI Ready	(1) USB
kWh	.001kWh~99999.999kWh, (+/- 1% @50W~8000W) kh=1.0	Info. Display	Monochrome OLED
Dimension/Weight		Operation	
Net Size	432 x 458 x 44.45 mm	Operation Temp.	0 ~ 45°C
Net Weight	10.0 kg	Operation Humid.	0% ~ 90% RH
Package Size	620 x 535 x 160 mm	Storage Temp.	-20°C ~ 65°C
Package Weight	11.2 kg	Storage Humid.	0% ~ 90% RH
Approval			
Certification	FCC		
Warranty	2 years		

## Package

No	Description
1	PDU 1 set
2	Rack mount accessories 1 set
3	Software, manual, MIB by link below



## Optional Accessory

Model Number	Model Name
CPM-ENV-2	Temp./Humidity probe



## Line Drawing

